

Yoyang Inc. reserves the right to change the product described in this datasheet. All information contained in this datasheet is subject to change without prior notice. Yoyang Inc. assumes no responsibility for the use of any circuits shown in this datasheet.

### FSK Transmitter Module

The TXF-060U ISM band data transmitter is an ideal design module used for Car Alarm, Security System, and Remote controller, etc..

#### Main Function

- Complete with 1 crystal and 1 SAW Filter design
- Frequency Band: 315/434/868/915MHz
- Any 2 Lever formats
- Data rate from 300bps to 10Kbps.
- High Power output up to 6 dbm
- Low power consume Max 20mA at 3V
- Wide operate temperature from -20°C -- +70°C
- Small size



#### Specification

Description	Part No: TXF-060U
Frequency stability	30ppm at 25°C
Operation frequency	315MHz or 434MHz or 868MHz or 915MHz
Data Rate	300bps to 10Kbps.
Modulation	± 30K for wide band FSK, ± 4.5K for narrow band FSK
Channel spacing	100KHz for wide band, 25KHz for narrow band
Working Voltage	3V ± 10%
RF power output	6dBm (4mW).
Power consumption	TX ON 20-25 mA.
Working temperature range	-20°C-+70°C.
Module Size	44mm X 12mm X 6mm.
Weight	4 grams.



### Pin Description

Pin Number	Name	Description
1	ANT	RF Output to antenna
2	GND	GND
3	GND	System Ground
4	VCC	Power Supply DC V+ 3V
5	Data	Transmitter Data
6	TX	TX Enable (Hi to TX ON)
7	GND	Ground

Pin Lead size: 2.54mm 7 pin single

### PCB Size and Pin Assignment

